



COMPRESSION LATCH STAINLESS STEEL 22 MM

Quarter-turn compression latch. Available both with clockwise or counter clockwise action to open. Close and tighten with a single continuous half-turn motion. First 90° turn moves the cam 90°, the second 90° turn retracts the cam 6 mm. Protection degree IP65, also classed waterproof according to NEMA 4. Latch is supplied assembled and with screw with mechanical thread lock.



MATÉRIAU

Cam: Acier inoxydable 304
Housing: Acier inoxydable 316
Insert: Acier inoxydable 316
Écrou: Acier inoxydable 304
Vis : Acier inoxydable 304

RELATED PRODUCTS

Similar products: 2-135, 2-136, 6-135, 6-136
Cams: 2-481
 Use the Index Code at industrilas.com

TESTS & STANDARDS

Cutout: COMBI
Standards: IP66, NEMA 4, DIN EN 61373
Torque:

Make your selections in each column to create your article number (AABBCC-DEFF-HHLL)

AA Description	BB Matériau	CC Type de came	D Rotation d'ouverture	E Écrou	FF Insert	HHLL H/L en mm
24 Loquet à compression	90 Inox 316	77 Position de came fixe	2 Sens anti-horaire 3 Sens horaire	0 Écrou standard	09 Carré 8	0000 Sans came
						0845 8 / 45
						1045 10 / 45
						1245 12 / 45
						1445 14 / 45
						1645 16 / 45
						1845 18 / 45
						2045 20 / 45
						2245 22 / 45
						2445 24 / 45
						2645 26 / 45
						2845 28 / 45
						3045 30 / 45
						3245 32 / 45
						3445 34 / 45
						3645 36 / 45
						3845 38 / 45
4045 40 / 45						
4245 42 / 45						
4445 44 / 45						
4645 46 / 45						
4845 48 / 45						
5045 50 / 45						
5245 52 / 45						
5445 54 / 45						