



#### **MATERIAL**

Anti Vibration Bushing: TPE Bushing: Steel, zinc plated

**Cam:** Hardened steel, anti-friction coating **Clip:** Glass fibre reinforced polyamide

(PA6GF30)

Housing: Steel, zinc plated Striker: Steel, zinc plated Trigger: Hardened steel, zinc plated

### **RELATED PRODUCTS**

Needed components for a complete system: 2-850, 2-745, 2-746, 2-835, 2-860
Similar products: 2-750-01, 2-750-02, 2-


750-04, 2-750-07

Use the Index Code at industrilas.com

# VECTOR ROTARY LATCH - INLINE PERPENDICULAR PULL

Vector rotary latches offer concealed latch points with convenient push-to-close action. Vector Rotaries are suitable for a variety of applications that require high strength, robust and secure latching. They are employed either as single latch point or in a multipoint latching system. Available in either single or two stage latching. The two stage rotary offers a safety feature that securely latches a partially latched compartment. Specially engineered to offer minimized trigger release force that ensures smooth and easy opening.

Vector rotaries are combined with Vector actuators that connect to the rotary latch by Vector rods or cables, creating an optimized latching system with components easily and securely fitted together. Please see related products to choose your components for your complete Vector rotary latching system.





## INDUSTRILAS.COM

# Make your selections in each column to create your article number (AAAA-BBCDEFFG-HH)

AAAA	Туре	ВВ	Material	C Type	D Type of jaw	E Mounting hole	FF Trigger	G Left/ Right	НН	Striker
5223	Rotary for 9,4 mm striker	11	Steel, zinc plated	1 Single stage	Single 1 jaw	O Through hole	Inline 03 Perpendicular	1 Right		No striker
5224	Anti-BSR* Rotary for 9,4			2 Double stage		1 M6 threaded	Pull	2 Left	01	With striker bolt UNC 5/16-18
	mm striker					2 UNC 1/4- 20			02	With striker bolt M8
									03	With looped striker
									04	With riveted striker

<sup>\*</sup> Anti-BSR means no Buzz, Squeak or Rattle due to TPE anti vibration bushing.

